



Door Entry



Entry Loop

Induction Loop System

Induction loop for the hard of hearing in the 4000 Series modular design with a nominal working distance of 0.5 metres.

An Introduction

The induction loop module connects to the Videx audio amplifier module to enable users with a hearing aid set to the T position to hear the tenant speak. The unit is built into a standard size 4000 Series module which means it can be used in conjunction with most other 4000 Series modules allowing a customized door panel to be constructed. The induction loop is also available for vandal resistant door panels. The unit has an internal aerial which eliminates the need for an external aerial loop making the installation much easier than a conventional loop system. The unit will operate on voltages of 12/24V AC or DC with a resting current of approx. 50mA.

Features:

- Modular design.
- Self contained.
- High visibility label to inform the user of the facility including basic instructions.
- Internal volume control.

Order Codes:

4000 Series induction loop module	4846/IND
Add facility to a VR panel	VR/IND

Note: For systems with a 4836, 4837, 4832, 4838, 136 or 437 amplifier the induction coil simply connects in series with the audio amplifier. Digital systems, 2 wire systems and the VK4K will require connections directly across the door panel speaker.

VIDEX SECURITY LIMITED,
1 Osprey, Trinity Park, Trinity Way, London, E4 8TD

NORTHERN OFFICE, Unit 4-7 Chillingham Industrial Estate, Chapman Street, Newcastle Upon Tyne, NE6 2XX
Tel 0870 300 1240 Fax 0191 224 5678 Sales 0191 2388 324 E-mail sales@videx-security.com Web www.videx-security.com

Once selected. Twice the support.