

CDV Series

PDN-345T **Electronic Directory**



- * **Up to 345 Numbers**
- * **Backlit LCD Display**
- * **Easy to Programme**
- * **Telephone Line or PABX**
- * **Stainless Steel Panel**
- * **Stand Alone**
- * **10 User Keypad Access**
- * **2760 User Proximity**
- * **4 Additional Reader Capacity**
- * **Weather Resistant**

The PDN-345T is a telephone entry system which connects directly to a dedicated telephone line or PABX extension. The unit is supplied in a rugged stainless steel housing (flush or surface), and has an integral proximity reader.

The unit is programmed either from the front keypad via a master programming password, or by a pc/laptop with the PDN software loaded. Optional modems can be fitted to provide remote programming. Up to 345 telephone numbers can be entered into the system, each number can be identified by alpha-numeric data shown on the LCD screen.

The integral proximity reader allows for standalone operation within the unit, or for connection to on-line systems running the UGL/UGM access control.

Door release is initiated from the receiving handset (traditional or mobile), and the system can be programmed with various options on answer.

The PDN-345T is a very cost effective unit, and only requires a telephone line and minimal installation time to complete.

Specification

Voltage:	12vac/dc
Current:	180mA active
Connection:	Standard "Land-Line" or GSM
Environmental:	IP65, -20 to +70C
Dimensions:	380 x 160 x 60mm
Finish:	Stainless Steel

Product Code

PDN-345T-F
PDN-345T-S
CIP
LOG-345T
BMU

Electronic Directory, Flush
Electronic Directory, Surface
Interface (required)
Software (optional)
PC/PDN Interface (optional)