

POSTS & ACCESSORIES

The extensive variety of mounting posts and accessories are designed to compliment the BPT entry ranges. The posts are all constructed in the UK from stainless steel and have consistently proven to be a hard wearing and stylish option for vehicle entrances, or where placing an entry panel to a wall or building is not practical. As well as a standard range of posts for vehicle, DDA, Pedestrian and HGV applications, custom posts can be manufactured for architectural requirements. It is also possible to powder coat any post to an applicable RAL finish to perfectly match the entry panel.

BPT also supply a large range of locks and accessories to complete any access system. Standard strike locks, magnetic locks and a number of specialist solutions are all available. Added to this, a selection of request to exit buttons and break glass units can all be ordered making bpt the complete access system provider.



CAME bpt

(-)

1 2 3
4 5 6
7 8 9
0 * #

Model: CAME BPT LK
Serial: 1234567890

Please press for assistance

Info
Assistance
Emergency
Service & Repair

1 2 3
4 5 6
7 8 9
0 * #

camebpt.co.uk

MOUNTING POSTS

Code	Description
TP/1200	1200mm slim line angled vehicle post. Produced from tubular steel (requires ADP adaptor plate and surface housing)
HDP/1200	1200mm angled vehicle post. Produced from 80mm box section stainless steel. (requires ADP adaptor plate and surface housing)
HDP/1400	1400mm custom made box post to suit flush mounted entry panels. For vehicle or wheelchair suitable applications. Face plate layout can be custom designed to suit a number of custom features (faceplate £POA)
HDP/1850	1850mm Custom made box post to suit flush mounted entry panels. For pedestrian or dual height wheelchair suitable applications. Face plate layout can be custom designed to suit a number of custom features (faceplate £POA)
HDP/2000	2000mm Dual height vehicle post for use with shared car and lorry entrances. Produced from 80mm box section stainless steel (requires ADP adaptor plates and surface housings)
HDP/DUAL	2000mm/1200mm Dual height HGV and vehicle post for use with shared car and lorry entrances. Produced from 80mm box section stainless steel (requires 2 x ADP adaptor plates and 2 x surface housings)
POST/1400	1400mm box section mounting post for standard size 1-4 entry panels. Particularly suited to the X1 DDA range of entry panels to ensure correct mounting height (surface housing required)
POST/1700	1700mm box section mounting post for standard size 1-4 entry panels. Particularly suited to pedestrian applications to ensure correct mounting height (surface housing required)
ADP/1	Adaptor plate for size one entry panels (use with TP/1200 and HDP 1200/2000 mounting posts)
ADP/2	Adaptor plate for size two entry panels (use with TP/1200 and HDP 1200/2000 mounting posts)
ADP/3	Adaptor plate for size three entry panels (use with TP/1200 and HDP 1200/2000 mounting posts)
ADP/4	Adaptor plate for size four entry panels (use with TP/1200 and HDP 1200/2000 mounting posts)

MOUNTING POSTS

For free standing panels at either pedestrian or vehicle entrances, a range of mounting posts are available. All posts are manufactured with a brushed steel finish, but can be coated to match most finishes.

A range of posts are held in stock and are available next day. For more bespoke solutions, integrated entry panels and mounting posts can be designed to meet your requirements.



HDP/DUAL



HDP/1200

POST/1700



HDP/1850



Bespoke HDP -
can include personalised
logos and engraving




TP/1200

POST/1400

POST/1700

LOCKS AND ACCESSORIES

STRIKE LOCKS (LATCH STYLE)





Price	Description	Price	
	Standard Electric Strike Lock MILOCK (Fail secure) <ul style="list-style-type: none"> • Power input: 12vDC or 12vAC • Current draw: 0.25A@12vDC • 250kg side force • Mortice or surface fitting 		Standard Electric Strike Lock MIUNLOCK (Fail safe) <ul style="list-style-type: none"> • Power input: 12vDC • Current draw: 0.25A@12vDC • 250kg side force • Mortice or surface fitting
	Monitored Electric Strike Lock MILOCKM (Fail secure) <ul style="list-style-type: none"> • Power input: 12vDC or 12vAC • Current draw: 0.25A@12vDC • 250kg side force • Monitored 		Monitored Electric Strike Lock MIUNLOCKM (Fail safe) <ul style="list-style-type: none"> • Power input: 12vDC • Current draw: 0.25A@12vDC • 250kg side force • Monitored
	Premium Electric Strike Lock LR/310L (Mortice) <ul style="list-style-type: none"> • Power input: 12vDC • Current draw: 0.25A@12vDC • 2000lbs jaw strength pull test • Fail Secure OR Fail Safe 		Premium Electric Strike Lock LR/350 (Surface) <ul style="list-style-type: none"> • Power input: 12vDC • Current draw: 0.25A@12vDC • 2000lbs jaw strength pull test • Fail secure OR Fail safe

MAGNETIC LOCKS

Price	Description	Price	
	Standard Magnetic Lock EM/10010 <ul style="list-style-type: none"> • Current draw: 0.5A@12vDC • Holding force: 1200lbs (545Kg) • Weight: 4.8kg • Unmonitored 		Standard Magnetic Lock EM/10020 <ul style="list-style-type: none"> • Current draw: 0.5A@12vDC • Holding force: 1200lbs (545Kg) • Weight: 4.8kg • Monitored
	Slimline Magnetic Locks EM/10001 <ul style="list-style-type: none"> • Current draw: 0.5A@12vDC • Holding force: 600lbs (272Kg) • Weight: 2kg • Unmonitored 		Slimline Magnetic Locks EM/10002 <ul style="list-style-type: none"> • Current draw: 0.5A@12vDC • Holding force: 600lbs (272Kg) • Weight: 2kg • Monitored
	Mortice (Flush) Mag Locks EM/10000 <ul style="list-style-type: none"> • Current draw: 0.5A@12vDC • Holding force: 600lbs (272Kg) • Weight: 2kg • Unmonitored 		Mortice (Flush) Mag Locks EM/10000R <ul style="list-style-type: none"> • Current draw: 0.5A@12vDC • Holding force: 600lbs (272Kg) • Weight: 2kg (mortice) • Monitored
	Double Magnetic Locks EM/10060 <ul style="list-style-type: none"> • Current draw: 0.5Ax2@12vDC • Holding force: 1200lbs (545Kg) x2 • Weight: 9.5kg • Unmonitored 		Double Magnetic Locks EM/10040 <ul style="list-style-type: none"> • Current draw: 0.5Ax2@12vDC • Holding force: 1200lbs (545Kg) x2 • Weight: 9.5kg • Monitored
	Slimline Double Mag Lock EM/10004 <ul style="list-style-type: none"> • Current draw: 0.5Ax2@12vDC • Holding force: 600lbs (272Kg) x2 • Weight: 4kg 		

LOCKS AND ACCESSORIES












MAGNETIC LOCK BRACKETS

Price	Description	Price	Description
	Standard Brackets EM/BR006 <ul style="list-style-type: none"> L bracket for use with standard magnets. Adjustable for outward opening doors 		Standard Brackets EM/BR026 <ul style="list-style-type: none"> Z & L brackets for use with standard magnets. Inward opening doors only
	Slimline Brackets EM/BR300L <ul style="list-style-type: none"> L bracket for use with slimline magnets. Adjustable for outward opening doors 		Slimline Brackets M/BR089 <ul style="list-style-type: none"> Z & L brackets for use with slimline magnets. Inward opening doors only

SPECIALISTS LOCKS

Price	Description	Price	Description
	External Magnetic Lock EM/GATE-F <ul style="list-style-type: none"> Power input: 12vDC/24vDC Current draw: 0.46A@12vDC Holding force: 1200lbs (545kg) Weight: 4.8kg Monitored 		External Magnetic Lock EM/GATEZL <ul style="list-style-type: none"> Z & L mounting brackets for EM/GATE-F magnets
	Electric Bolt Lock EB/FS <ul style="list-style-type: none"> Power input: 12vDC Current draw: Pull in 0.9A Holding 0.3A@12vDC Fail safe 		Electric Bolt Lock EM/BR300L <ul style="list-style-type: none"> Power input: 12vDC/24vDC Current draw: Pull in 0.9A Holding 0.3A@12vDC Fail safe Narrow width

ACCESSORIES

Price	Description	Price	Description	Price	Description
	RTE/2 <ul style="list-style-type: none"> Single gang stainless steel 'Press To Exit' NO/NC 		RTE/2VR <ul style="list-style-type: none"> Single gang stainless steel VR button 'Press To Exit' NO/NC 		RTE/3 <ul style="list-style-type: none"> Doorbell style stainless steel VR button 'Press To Exit' NO/NC
	DDA/RTE <ul style="list-style-type: none"> Single gang tactile plastic cover plate for use with RTE/2 & RTE/2VR 'Press To Exit' 		RTE/P22 <ul style="list-style-type: none"> Single gang plastic 'Press To Exit' 		RTE/P3 <ul style="list-style-type: none"> Doorbell style plastic 'Door Release'
	VRFS/DL <ul style="list-style-type: none"> Firemans Drop key switch Flush mount (Key not included) 		VRFS/DLSURF <ul style="list-style-type: none"> Firemans Drop key switch Surface mount (Key not included) 		VRFS/KEY <ul style="list-style-type: none"> Firemans Drop key
	BG/1GRNR <ul style="list-style-type: none"> Surface mount green break glass unit Resettable 		R1 <ul style="list-style-type: none"> Double pole, Double throw clean contact relay. Two outputs 2 Amp rating per output (@24vDC) 		