

System 300 Analogue Video Control Equipment

XAV/300 Video Modulator

The unit enables the video signal, coming from the devices suitable for the system 300 (e.g. video module MVT/300, etc.) to be modulated on the receivers twisted pair.

Item Details

| | | | |
|------------|--------|-----------------------------|----------------|
| Width | 145mm | Minimum working temperature | 0°C |
| Height | 70mm | Maximum working temperature | +35°C |
| Depth | 64.5mm | Mounting type | DIN guide |
| Weight | 0.25kg | Minimum package quantity | 1 |
| Module DIN | 4 | Certification CE | Yes, certified |



XDV/300A Video Amplifier

Unit for restoring or repeating the modulated video signal distributed by means of the twisted pair.

Item Details

| | | | |
|------------|--------|-----------------------------|----------------|
| Width | 60mm | Minimum working temperature | 0°C |
| Height | 44mm | Maximum working temperature | +35°C |
| Depth | 6mm | Mounting type | DIN guide |
| Weight | 0.05kg | Minimum package quantity | 1 |
| Module DIN | 1 | Certification CE | Yes, certified |



XDV/303 Video Distributor

Distributor for balanced video signal suitable for splitting or concentrating lines conveying video signals.

Item Details

| | | | |
|------------|--------|-----------------------------|----------------|
| Width | 145mm | Minimum working temperature | 0°C |
| Height | 140mm | Maximum working temperature | +35°C |
| Depth | 64.5mm | Mounting type | DIN guide |
| Weight | 0.50kg | Minimum package quantity | 1 |
| Module DIN | 8 | Certification CE | Yes, certified |



XDV/304 Video Distributor - 4 Outputs

Unit for the distribution of the modulated video signal over 4 lines via twisted pair.

Item Details

Width 60mm
Height 44mm
Depth 16mm
Weight 0.07kg
Module DIN 1

Minimum working temperature 0°C
Maximum working temperature +35°C
Mounting type DIN guide
Minimum package quantity 1
Certification CE Yes, certified

