

TECHNICAL DATA SHEET

VRDI63M

True Day/Night Vandal Resistant IR Dome Camera with Magnetic Ball Gimbal



Magnetic Ball Gimbal Illustration



WB-163M

KEY FEATURES

- 1/3" Sony Super HAD CCD
- Ultra High Resolution, 600 TVL
- WideLux DSP
- Vandal Resistant Housing
- 100mm Polycarbonate Bubble
- 3-Axis Magnetic Ball Gimbal
- Mechanical IR Cut-Filter
- Intelligent IR Control
- WideLux sWDR (Super Wide Dynamic Range)
- 3D DNR (Digital Noise Reduction)
- Integrated 3.3-12mm DC AIVF Lens
- 10 IR LED Pcs (20m Illumination*)
- Highlight Eclipse Function
- Motion Detection
- Privacy Function
- O.S.D.
- RS-485 Interface
- Dual Mount (Surface/Flush)
- IP66 Rated
- DC 12V / AC 24V
- Wall Bracket Available (Optional)

*Illumination distance quoted above is based on optimal conditions

ORDERING INFORMATION

- VRDI63M True Day/Night WDR IR Vandal Dome with Magnetic Ball Gimbal, Dual Voltage
- VRDI63M/RC OSD Remote Controller for Dome
- WB-163M Wall Bracket for VRDI63M Dome

WIDELUX WDR

Achieves better optimal horizontal and vertical resolution. It balances wide dynamic process, resolving detail under a wider range of lighting environments.

INTELLIGENT IR CONTROL

Prevents oversaturation when objects come close to the camera allowing background details to remain visible.

TECHNICAL DATA SHEET

TECHNICAL SPECIFICATION

Model Number	VRD163M
Image Sensor	1/3" Sony Super HAD CCD
Horizontal Resolution	600 TVL (Day), 650 TVL (Night)
Min. Illumination (F1.2)	0.1 Lux (Sens-up Off), 0.0001 Lux (Sens-up, x512)
Lens	3.3 - 12mm DC AI Varifocal Lens
Effective Pixels (H x V)	752 x 582
Shutter Speed	1/50 ~ 1/120,000 Seconds
Scanning System	625 Lines, 2:1 Interlace
Synchronisation	Internal
Frequency	Horizontal: 15.625KHz Vertical: 50.00Hz
Video Output	1.0Vp-p Composite 75Ω
S/N Ratio	>52dB (AGC Off)
White Balance	Auto ATW / Push Lock / Manual (1,800°K~11,000°K)
Gain Control	Standard: -6dB ~ 34dB Auto / Maximum
Iris Control	DC Iris
WideLux WDR	On / Off (Selectable)
3D DNR	On / Off (Selectable)
Sens-up	2x ~ 512x / Off
Digital Zoom	x1 ~ x8
Motion Detection	On / Off (8 Zones)
Privacy Mask	On / Off (8 Zones)
RS-485 Interface	Yes (Pelco D)
IP Rating	IP66
IR LEDs & Illumination (850nm)	10 Pcs IR LEDs / 20m Illumination Range*
Operating Conditions	Temperature: -10°C ~ +50°C, Humidity: 0 ~ 80% RH
Power Supply	DC 12V / AC 24V
Power Consumption	90mA / 24VAC (IR Off); 190mA / 24VAC (IR On); 200mA / 12VDC (IR Off); 400mA / 12VDC (IR On)
Dome Dimensions	(D x H) 150 x 115.7 mm
Weight	1.9Kg
Wall Bracket Dimensions & Weight	(W x H) 240mm x 191 mm, 1.3Kg

Features and specifications are subject to change for further improvement without any notice

*Illumination distance quoted above is based on optimal conditions