

TECHNICAL DATA SHEET

VRD43/12

Super High Resolution Digital Day/Night Vandal Dome Camera



VRD Dome



VRD Dome with Wall Bracket



VRD Dome with Junction Box

KEY FEATURES

- 1/3" NEXT CHIP
- Super High Resolution, 540 TVL
- Vandal Resistant Housing
- 100mm Polycarbonate Bubble
- Digital Day/Night
- Integrated 4-9mm DC AI VF Lens
- Gain Control
- Electronic Shutter Control
- Auto White Balance
- Improved Cable Entry
- Rubber Seal Footprint
- Three Axis Camera Positioning
- IP67 Rated
- DC 12V

ORDERING INFORMATION

VRD43/12	Day/Night Vandal Dome with 4-9mm DC AI VF Lens, DC12V
WB-VRD	Wall Bracket for VRD Domes
VRD-JB	Junction Box for VRD Domes



TECHNICAL DATA SHEET

TECHNICAL SPECIFICATION

Model Number	VRD43/12
Image Sensor	1/3" NEXT CHIP
Horizontal Resolution	540 TVL
Min. Illumination	0.15 Lux (40 IRE)
Lens	4-9mm / F1.5 Varifocal Auto Iris
Effective Pixels (H x V)	752 x 582
Shutter Speed	Fixed (1/50)
Scanning System	2:1 Interlace
Synchronisation	INT
Frequency	Horizontal: 15.625KHz Vertical: 50.00Hz
Video Output	1.0Vp-p~75Ω (Video 0.7Vp-p Sync 0.3Vp-p)
S/N Ratio	>50dB (AGC Off)
White Balance	AWB (1800°K~10500°K)
Gain Control	ON
Iris Control	DC
IP Rating	IP67
Total Pixels (H x V)	795 x 596
Operating Conditions	Temperature: -10°C ~ +50°C Humidity: 30 ~ 90% RH
Power Supply	DC 12V
Power Consumption	160 mA
Dimensions (D x H)	152.0 x 104.7 mm
Weight	910g

Features and specifications are subject to change for further improvement without any notice